









## Single row radial ball bearings - Metric (Continued)



### Cages and shields

- Available
- Feasible (minimum quantity)
- Out of program

Dimensions d D B	rs	Designation	Limiting speeds rpm x 1'000			Basic load ratings		Balls	Abutment dimensions		Mass ~ gr	Designation	Cage Y Shields							Cage J Shields							Cage T9H Shields							Cage TBH Shields								
			Oil	Grease	Contact seals	Dyn. Cr kN	Stat. Cor kN		da min mm	Da max mm			Open	Z	2Z	RSR	2RSR	RSF	2RSF	RSV	2RSV	Open	Z	2Z	RSR	2RSR	RSF	2RSF	RSV	2RSV	Open	Z	2Z	RSR	2RSR	RSF	2RSF	RSV	2RSV			
mm inch	min							mm inch	mm inch																																	
<b>15</b> 24 .945	5 .197	<b>61802</b>	34	28	16	2.070	1.260	14x3/32"	17.0 .669	22.0 .866	8.0	<b>61802</b>																														
24 .945	6 .236	<b>62802</b>	34	28	16	2.070	1.260	14x3/32"	17.0 .669	22.0 .866	9.4	<b>62802</b>																														
24 .945	7 .276	<b>63802</b>	34	28	16	2.070	1.260	14x3/32"	17.0 .669	22.0 .866	10.9	<b>63802</b>																														
28 1.102	7.0 .276	<b>61902</b>	32	26	15	4.330	2.250	10x5/32"	17.0 .669	26.0 1.024	14.8	<b>61902</b>																														
32 1.260	8 .315	<b>16002</b>	30	24	14	5.590	2.840	9x3/16"	17.0 .669	30.0 1.181	27.7	<b>16002</b>																														
32 1.260	9 .354	<b>6002</b>	30	24	14	5.590	2.840	9x3/16"	17.0 .669	30.0 1.181	30.7	<b>6002</b>																														
32 1.260	13 .512	<b>63002</b>	30	24	14	5.590	2.840	9x3/16"	17.0 .669	30.0 1.181	42.6	<b>63002</b>																														
35 1.378	11 .433	<b>6202</b>	26	20	13	7.730	3.760	8x6mm	19.0 .748	31.0 1.220	47.5	<b>6202</b>																														
35 1.378	14 .551	<b>62202</b>	26	20	13	7.730	3.760	8x6mm	19.0 .748	31.0 1.220	58.6	<b>62202</b>																														
<b>17</b> 26 .669	5 1.024	<b>61803</b>	32	26	15	2.230	1.460	16x3/32"	19.0 .748	24.0 .945	8.8	<b>61803</b>																														
26 1.024	6 .236	<b>62803</b>	32	26	15	2.230	1.460	16x3/32"	19.0 .748	24.0 .945	10.4	<b>62803</b>																														
26 1.024	7 .276	<b>63803</b>	32	26	15	2.230	1.460	16x3/32"	19.0 .748	24.0 .945	12.0	<b>63803</b>																														
30 1.181	7.0 .276	<b>61903</b>	30	24	14	4.600	2.550	11x5/32"	19.0 .748	28.0 1.102	16.0	<b>61903</b>																														
35 1.378	8 .315	<b>16003</b>	28	22	13	6.000	3.250	10x3/16"	19.0 .748	33.0 1.299	33.3	<b>16003</b>																														
35 1.378	10 .394	<b>6003</b>	28	22	13	6.000	3.250	10x3/16"	19.0 .748	33.0 1.299	40.5	<b>6003</b>																														
35 1.378	14 .551	<b>63003</b>	28	22	13	6.000	3.250	10x3/16"	19.0 .748	33.0 1.299	54.9	<b>63003</b>																														
40 1.575	12 .472	<b>6203</b>	22	18	12	9.550	4.760	8x17/64"	21.0 .827	36.0 1.417	69.5	<b>6203</b>																														

**1** Basic load ratings and number of balls are different

### PRECISION BALL BEARINGS STANDARD AND SPECIAL

WIB SA, Champ-Barby 61, 1630 BULLE, Switzerland

Tel: (+41) 26 919 11 22, Fax: (+41) 26 919 11 20

http://www.wib-bearings.com info@wib-bearings.com